











3pins/4pins M8 Field wirable connector



Field wireable connector	Type NO.	ID NO.	Features	Pinout
Straight Female Screw terminals 	SK3212-0	10091500	PA6+GF,Black/Brass M10 Cable gland Accept 3.5~5mm cable diameter Screw terminals 85°C , 60V, 4 A	
	SK4212-0	10091501	PA6+GF,Black/Brass M10 Cable gland Accept 3.5~5mm cable diameter Screw terminals 85°C , 60V, 4 A	
Straight Male Screw terminals 	SZ3212-0	10091502	PA6+GF,Black/Brass M10 Cable gland Accept 3.5~5mm cable diameter Screw terminals 85°C , 60V, 4 A	
	SZ4212-0	10091503	PA6+GF,Black/Brass M10 Cable gland Accept 3.5~5mm cable diameter Screw terminals 85°C , 60V, 4 A	
Straight Female Solder cup 	SK3212-0/L	10091504	PA6+GF,Black/Brass M10 Cable gland Accept 3.5~5mm cable diameter Solder cup 85°C , 60V, 4 A	
	SK4212-0/L	10091505	PA6+GF,Black/Brass M10 Cable gland Accept 3.5~5mm cable diameter Solder cup 85°C , 60V, 4 A	
Straight Male Solder cup 	SZ3212-0/L	10091506	PA6+GF,Black/Brass M10 Cable gland Accept 3.5~5mm cable diameter Solder cup 85°C , 60V, 4 A	
	SZ4212-0/L	10091507	PA6+GF,Black/Brass M10 Cable gland Accept 3.5~5mm cable diameter Solder cup 85°C , 60V, 4 A	

3pins/4pins M8 Field wirable connector



Field wireable connector	Type NO.	ID NO.	Features	Pinout
Angled Female Solder cup 	SLK3212-0/L	10091508	PA6+GF,Black/Brass M10 Cable gland Accept 3.5~5mm cable diameter Solder cup 85°C , 60V, 4 A	
	SLK4212-0/L	10091509	PA6+GF,Black/Brass M10 Cable gland Accept 3.5~5mm cable diameter Solder cup 85°C , 60V, 4 A	
Angled Male Solder cup 	SLZ3212-0/L	10091510	PA6+GF,Black/Brass M10 Cable gland Accept 3.5~5mm cable diameter Solder cup 85°C , 60V, 4 A	
	SLZ4212-0/L	10091511	PA6+GF,Black/Brass M10 Cable gland Accept 3.5~5mm cable diameter Solder cup 85°C , 60V, 4 A	
Straight Female Screw terminals 	SK3218-0	10093082	PA6+GF,Brass/Nickel PG7 Cable gland Accept : 3.5-5 mm cable diameter Solder cup 85°C , 60V, 4 A	
	SK4218-0	10093084	PA6+GF,Brass/Nickel PG7 Cable gland Accept : 3.5-5 mm cable diameter Solder cup 85°C , 60V, 4 A	
Straight Male Screw terminals 	SZ3218-0	10093083	PA6+GF,Brass/Nickel PG7 Cable gland Accept : 3.5-5 mm cable diameter Screw terminals 85°C , 60V, 4 A	
	SZ4218-0	10093085	PA6+GF,Brass/Nickel PG7 Cable gland Accept : 3.5-5 mm cable diameter Screw terminals 85°C , 60V, 4 A	